



NAUTIZ X1

FULLY RUGGED HANDHELD

FEATURES INCLUDE:

- 4" WVGA Sunlight Readable Display
- Texas Instruments OMAP 4430 CPU
- 1GB Memory & 4GB Flash Storage
- MIL-STD-810G & IP67
- -20°C to 60°C Operating Temperature
- Android / Windows Embedded OS



BUILT TO SURVIVE

The Nautiz X1[®] is an ultra-rugged, ultra-compact handheld built for professional work in harsh environments.

It breaks through barriers of size, toughness and reliability to offer field professionals the proven ruggedness of a Nautiz ultra-rugged handheld that runs the Android 4.0 (Ice Cream Sandwich) or Windows Embedded Handheld 6.5 operating system.

With the Nautiz X1, you don't have to choose between dependability and slim design. With its small size and light weight of only 180 grams (6.3 ounces), it's among the smallest enterprise handhelds.

Built for the toughest conditions, the Nautiz X1 meets stringent MIL-STD-810G military standards for withstanding humidity, vibration, drops and extreme temperatures.

And with an IP67 rating, the Nautiz X1 is fully waterproof and impervious to dust and sand.

SPECIFICATION

CPU Option(s)	Texas Instruments OMAP 4430 (1 GHz)
Memory	1GB Memory Onboard
Storage	4GB Flash Onboard
I/O Interface	Micro USB 2.0 OTG 5 Pin USB Docking Connector 5 MP Camera With Autofocus & LED Flash
Expansion	MicroSD / MicroSDHC Slot (User Accessible)
PAN	BT v2.1
Wireless LAN	802.11 b/g/n Supports WEP, WPA, WPA2
Navigation	Integrated u-blox® GPS, WAAS/EGNOS/MSAS-capable, G-Sensor, E-Compass
Cellular (WWAN)	GSM/GPRS/EDGE, UMTS/HSPA+
PAN	BT 2.1 EDR
Battery	Standard: 1530 mAh (5.66 Wh) Li-Ion Optional: 3060 mAh (11.32 Wh) Li-Ion

Display	4" WVGA Sunlight Readable Display
Resolution	854 x 480
Brightness	Sunlight Readable
Touchscreen	Capacitive Touch Screen
Temperature	Operating: -30 °C to 60 °C Storage: -40 °C to 70 °C
Software	Android 4.0 (Ice Cream Sandwich) Windows Embedded Handheld 6.5
Drop	26 drops from 1.22 m (4 ft) MIL-STD-810G Method 516.6, Procedure IV
Vibration	MIL-STD-810G Method 514.6, Procedure I
Altitude	4572 m (15,000 ft) MIL-STD-810G, Method 500.5 Procedure I
Sand & Dust	IP67
Water	IP67
Dimensions (W x D x H)	125 mm x 15 mm x 65 mm
Weight	180 g



NAUTIZ_X1_Datasheet_Rev1.pdf

Technical Specifications quoted are verified but do not indicate the maximum performance limitations of the equipment. Specifications are subject to change without notice. E & OE Issue A

